## Environmental Resources Management, inc.



855 Springdale Drive • Exton, Pennsylvania 19341 • (215) 524-3500 • Telex 4900009249

16 February 1989

Ms. Janet Feldstein
U.S. Environmental Protection Agency
Region II
Emergency and Remedial Response Division
Room 737
26 Federal Plaza
New York, NY 10278
File No: 8

File No: 802-01-00-01

Dear Janet:

Enclosed for your use is a revised page 4-8 of the Work Plan for the Feasibility Study/First Operable Unit of the SCP/Carlstadt Site. Please discard page 4-8 which you received on Wednesday and replace it with the attached sheet. Four additional copies are included for insertion into your copies. Thank you.

If you have any questions/comments, please contact Mr. Gil Weil at (201) 563-5905, or me at (215) 524-3521. Thank you.

Sincerely,

Marian E. Donovan Carlin

Marian E. Donovan Carlin Project Manager

MEDC/jkp

Enclosures

cc: Pam Lange (3 enclosed)
Harry Yeh (2 enclosed)
Gil Weil (enclosed)
Ron Fender (enclosed)
Bill Warren
Susan Hoffman (enclosed)



Performance trials will consist of a series of continuous-stir tests designed to determine the effect of the following process variables on the efficiency of extraction: type of extraction fluid, the fluid to soil volume ratio, the number of successive extractions, the sequence for using various extraction fluids (if more than one fluid is used), and the contact time in each extraction stage. Performance trials will be preceded by a chemical analysis of the raw soils and sludge. The procedure for each continuous-stir test is as follows:

- Fill a flat-bottomed flask with a known weight of prepared soil sample (after grinding and homogenization).
- Add a known volume of a single extraction fluid of known composition to the flask;
- 3. Stir the soil/fluid mixture to make a slurry, using a stirring bar/rotating magnet stirrer (or the equivalent);
- 4. Extract by continuously stirring the slurry for a preselected contact time;
- 5. Allow the slurry to settle into its soil and extraction fluid phases, and vacuum-filter the soil through filter paper;
- 6. As a specified volume of spent extraction fluid is transferred out of a selected extraction stage, analyze the fluid and record results in grams removed per kilogram of test material on a dry weight basis;
- 7. Conduct a number of continuous-stir tests simultaneously in order to compare treatment efficiency as a result of varying a single process variable. Conduct additional stir tests to assist in refining the processing conditions.
- b. Treatability Data Evaluation



## mental Resources Management, inc. Er.

855 Springdale Drive • Exton. Pennsylvania 19341 • (215) 524-3500 • Telex 4900009249

15 February 1989

Ms. Janet Feldstein U.S. Environmental Protection Agency Region II Emergency and Remedial Response Division Room 737 26 Federal Plaza New York, NY 10278

File No: 802-01-00-01

## Dear Janet:

Enclosed for your use and review is the Nork Plan for the Feasibility Study/First Operable Unit of the SCP/Carlstadt Site. four additional copies are included for your use. The Work Plan for the FS/FOU dated 15 February 1989, supersedes the Work Plan dated 16 December 1988.

If you have any questions/comments, please contact Mr. Gil Weil at (201) 563-5905, or ne at (215) 524-3521. Thank you.

Sincerely,

Marian & Donovan Carlin

Marian E. Donovan Carlin Project Manager

MEDC/jkp

Enclosures

Pam Lange (3 enclosed) Harry Yeh (2 enclosed) Gil Weil (enclosed) Ron Fender (enclosed) Bill Warren Susan Hoffman (enclosed)



## Ervionssental Resources Management, Inc.

Tololax (:

JOYNER PAGE

JOYNER PAGE (215)524-7335 GANET TE Attention: Company: Fex No.: (2/2) 264. From: MARIAN Work Order # 802-0/-0
(Please Included) Number of Pages INCLUDING c NOTES: Please send to TANET - 5 COPIES ARE YOU TODAY VIA you did not receive ase call (215) 524-3548 as soon as pos